

DOWNLIGHT RECESSED

 FLUX



## ZENIUS WASHER SMALL TRIM R027/R029



### APPLICATIONS

- ARCHITECTURAL HIGHLIGHTING
- DIRECT ILLUMINATION
- SHOP WINDOWS LIGHTING
- DRESSING ROOM
- SHOWCASE LIGHTING
- COVE LIGHTING

### FEATURES

- CUSTOMIZABLE FINISHING
- WIDE COLOR TEMPERATURE SPECTRUM
- IP20
- UNIFORM LIGHT DIFFUSION
- LED CONFIGURATION



For more information please check our website [www.fluxitalia.com](http://www.fluxitalia.com)  
or contact us tel.+39 071 0960086 email: [info@fluxitalia.com](mailto:info@fluxitalia.com)  
via Armando Cingolani, 13 Zona ind.le Sambucheto di Recanati 62019 Recanati (MC) - Italy


PRODUCT INFO

R027/R029

R027



R029



TECHNICAL DATA


LED TYPE	COB
POWER MAX	7W
LUMINOUS FLUX (lm)*	420lm
LUMINOUS EFFICIENCY (lm/W)*	60
COLOUR RENDERING INDEX (RA)	CRI>90
LED COLOUR (K)	2700K - 3000K - 3500K - 4000K
STEP MCADAM	SDCM 2
AVERAGE OPERATIONAL LIFE	50.000 HRS
OPTIC	LENS
BEAM ANGLE	15° - 24° - 36° - 50°
LIGHT DISTRIBUTION	SYMMETRIC
LIGHT DIRECTION	ADJUSTABLE 5°
IP PROTECTION GRADE	IP20
TYPE OF INSTALLATION	RECESSED
DRIVER	REMOTE
FOR EMERGENCY LIGHTING	SUITABLE
CUT HOLE (mm)	Ø 55

\*refers to max W / 3500K / 24°

■ 55X55




DRAWINGS



COLORS

STANDARD



ON REQUEST



ACCESSORIES

R027/R029

REFLECTORS




LENS FILM



FRESNEL  
0081



FROSTED  
0082



HONEYCOMB  
0083

